

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A61B 17/04, A61F 2/24</b>		<b>A1</b>	(11) International Publication Number: <b>WO 97/10757</b>
			(43) International Publication Date: 27 March 1997 (27.03.97)
(21) International Application Number: <b>PCT/US96/15026</b>		(81) Designated States: US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 19 September 1996 (19.09.96)		<b>Published</b> With international search report.	
(30) Priority Data: 60/004,163      22 September 1995 (22.09.95)      US			
(71) Applicant (for all designated States except US): AUTOGEN-ICS [US/GB]; Building 5, Kelvin Campus, West of Scotland Science Park, Glasgow G20 0SP (GB).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): DAHL, Terry, J. [US/US]; 2508 Janin Way, Solvang, CA 93463 (US). LEMP, Steven, K. [US/US]; 222 Santa Ynez Court, Santa Barbara, CA 93103 (US). SUGGITT, Robert, W. [US/GB]; 8 Lawn Park, Milngavie G62 6HG (GB).			
(74) Agent: ALTMAN, Daniel, E.; Knobbe, Martens, Olson and Bear, 16th floor, 620 Newport Center Drive, Newport Beach, CA 92660 (US).			

(54) Title: SEWING RING WITH INTEGRAL RETAINING SPRINGS

(57) Abstract

A sewing ring (14) of the present invention is used with an outer stent frame (12) to be mated with an inner stent (10) and tissue to form a tissue heart valve. The sewing ring (14) comprises an elastic ring (42) which is provided with a plurality of retaining springs (16, 18) which are encapsulated within a side of the elastic ring (42). This spring side of the elastic ring (42) is received in a corresponding plurality of grooves (44, 46) in a base of the outer stent frame (12) prior to the ultrasonic welding of a covering around the outer stent frame (12) and sewing ring (14). Preferably, the springs (16, 18) are formed into circles with spring ends (36, 38) joined via hooks formed by the last half coils of each end. The spring (16, 18) are preferably insert molded into the silicone elastomeric material of the elastic ring. The sewing ring and retaining springs configuration reduces the propensity of the retaining springs to uncouple, to translate circumferentially in the groove, and to vibrate against and damage the groove during the ultrasonic welding of the fabric covering. Thus, the optimum clamping force on the tissue placed between the inner and outer stents is maintained.



Best Available Copy

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## SEWING RING WITH INTEGRAL RETAINING SPRINGS

### Background of the Invention

5 This invention relates to the fabrication of bioprosthetic heart valve replacements. Valve replacements are required for patients having a heart valve which is diseased or otherwise incompetent. Commonly, heart valve bioprostheses are made from a combination of animal tissue and mechanical elements. These bioprostheses have an advantage over purely mechanical valves in that they do not require the use of anticoagulant therapy that plagues purely mechanical valves.

10 U.S. Pat. No. 5,163,955 (the '955 patent) discloses such a bioprosthetic valve, in which an inner stent, on which the tissue used to construct the valve is wrapped, is inserted into a spreadable outer stent containing a self-adjusting retaining spring around the circumference of its base. The inner stent posts are fitted with a plurality of outwardly-projecting pegs which register with holes cut in the tissue, and the inner stent assembly is covered with cloth. The spread outer stent clamps the stents together at its base and at a plurality of posts projecting from the bases of both the  
15 inner and outer stents. This clamping thus secures the tissue while compensating for irregularities and supplying a clamping force which is evenly distributed over the entire circumference of the tissue.

20 The outer stent disclosed in the '955 patent has an annular base constructed with a groove around its circumference, into which a self-adjusting retaining means such as a garter spring is fitted. The garter spring provides a clamping force when the inner stent is inserted into the outer stent. Additionally, the posts on the outer stent are configured with windows surrounded by struts, which give shape to the post. The window is shaped to conform to the shape of the inner stent posts while  
25 leaving a small gap between the inner stent posts and the struts when the inner stent is inserted into the outer stent. Such an arrangement facilitates the insertion of the inner stent into the outer stent and provides for a uniform application of the clamping force to the tissue.

30 At the bottom of each of the windows in the outer stent posts are slots which segment the base into a plurality of arcuate portions. The slots enable the outer stent to be spread open so that it can easily be fitted over the inner stent without damaging the tissue during the valve assembly process.

An elastomeric sewing ring is attached to the base of the outer stent assembly to facilitate the sewing of the assembled heart valve into the patient. The entire

assembly is covered with a fabric cover, typically made out of DACRON, which is bonded to the bottom of the outer stent base.

5 The current assignee's international application entitled STENTS FOR AUTOLOGOUS TISSUE HEART VALVE, published as W0 95/16412 on June 22, 1995, discloses the provision of two retaining springs disposed around the circumference of the base of the outer stent to prevent the inner and outer stents from becoming unsecured if one of the springs breaks. A separate elastomeric sewing ring is positioned over the springs and around the base of the outer stent. Each retaining spring is a conventional toroidal-shaped spring which wraps around  
10 the base of the outer stent and the two ends of each spring connect at a spring joint where the two ends are screwed together.

However, since the fabric cover is thermally bonded to the outer stent by an ultrasonic welding process, the welding process can cause the springs to vibrate significantly and become uncoupled from the base of the outer stent. Moreover,  
15 determining when a spring has uncoupled is problematic since the spring is hidden by the DACRON covering. Thus, x-rays of the valve may be necessary to determine if the springs uncoupled. Furthermore, the vibrations from the welding process may cause the springs to rotate circumferentially around the base of the outer stent, thereby possibly moving the spring joint into one of the gaps in the base.

### Summary of the Invention

In accordance with the present invention, an improved sewing ring is provided which is disposed around the base of an outer stent of a tissue heart valve for clamping the outer stent to an inner stent and to facilitate the sewing of the  
25 assembled heart valve into the patient. The inner and outer stents cooperate to form a heart valve implanted into a patient, typically by the use of sutures. The present invention provides a sewing ring and retaining springs configuration which lessens or eliminates the propensity for the retaining springs to uncouple during the process of welding a fabric covering to the outer stent.

30 Preferably, the outer stent has a base including a plurality of slots. In one preferred embodiment, an elastic sewing ring is disposed around the base where an upper retaining spring and a lower retaining spring are incorporated into the elastic sewing ring by an insert molding or other suitable method. By expanding the elastic sewing ring, the sewing ring is placed over the base of the outer stent, thereby

providing a secure fit to the base. Alternatively, the sewing ring may be bonded to the base. The sewing ring may be made of silicone elastomer, and the sewing ring may have a generally triangular cross-section. The base of the outer stent is preferably constructed with a pair of grooves around its circumference, into which the upper and lower retaining springs within the sewing ring are fitted to act as a clamping force.

The provision of more than one retaining spring is an advantageous feature of the present invention which gives the valve redundancy, for if one spring breaks, another will continue to provide the outer stent's clamping force on the inner stent. However, the present invention may be used with only one retaining spring insert molded into the silicone sewing ring as well.

The incorporation of the retaining springs within the silicone sewing ring provides the advantage of holding the upper and lower retaining springs in place within the grooves and preventing the springs from uncoupling during the ultrasonic welding process. Furthermore, since the springs are encapsulated within the sewing ring, the springs do not damage the grooves of the base by vibrating against the grooves during the ultrasonic welding process. Having the springs insert molded into the sewing ring dampens the spring vibration during welding so that the springs do not damage the grooves. Also, the springs are encapsulated so that the elastic material of the sewing ring is placed inside the coils of the springs to take away any vibration of the springs during the welding process.

Another feature of the present invention which prevents the retaining springs from uncoupling at the spring joint is a reconfiguration of the end coils on each retaining spring so that the end coil loops are transverse to each other, ensuring that the spring ends remain coupled together. The last-half coil of each end of the spring is bent outward to form a hook, and then the two ends may be hooked together. Then, the gaps in the hooks may be closed to ensure that the spring does not uncouple.

### Brief Description of the Drawings

FIGS. 1a and 1b are side views of the spring joint used in the prior art for heart valves.

FIG. 2 is side view of an alternate spring joint used in the prior art for heart valves.

FIG. 3 is a side view of the spring joint of the retaining spring of the present invention.

FIG. 4 is a cross-sectional view of the sewing ring with integral retaining rings of the present invention.

5 FIG. 5 is a partial cross-sectional view of a portion of an outer stent of the present invention showing the sewing ring fastened to the outer stent.

FIG. 6 is an exploded view of an outer stent having a sewing ring with features of the present invention.

10 FIG. 7 is a perspective view of mated inner and outer stents using a preferred embodiment of a sewing ring of the present invention.

#### Detailed Description of the Preferred Embodiments

15 Inner and outer stents of the tissue heart valve have frames 10, 12, respectively constructed out of a thermoplastic material such as DELRIN or the like using injection molding to form the entire component using unibody construction techniques, instead of welding or the like to attach any protuberances. Unibody construction minimizes risk to the patient when compared to welding, since welded bonds can break more easily, leading to the injection of valve components or fragments into the bloodstream.

20 Once constructed, the outer stent frame 12 is integrated with other components, including the sewing ring 14 of the present invention which has a plurality of retaining springs 16, 18 incorporated within, and both frames are covered with a fabric 20 such as DACRON or the like, to form the completed inner and outer stents 10, 12 used in the valve assembly. FIG. 7 shows the mated stents without the tissue or fabric coverings.

25 Figures 1a, 1b and 2 illustrate prior art spring joints where left and right ends of the spring are twisted together to form a ring. Figures 1a and 1b show a five turn interconnect where left end 22 and right end 24 are twisted together to form a spring joint 26. Figure 1a shows two and one-half coils of both the left end 22 and the right end 24 overlap each other at the spring joint 26, forming a five coil overlap. 30 Similarly, Figure 2 shows a six turn interconnect where three coils of left end 28 and right end 30 are twisted together to form spring joint 32. These spring connections as well as similar ones are familiar to those of skill in the art.

Figure 3 illustrates the improved spring joint 34 of the present invention which prevents the springs 16, 18 from uncoupling. Preferably, the springs are

5 formed into circles with spring ends 36, 38 joined via hooks formed by the last half-coils of each end. As shown in Figure 3, the last half-coil of left end 36 has been twisted from its conventional direction to form a hook, as has the last half-coil of right end 38 of the springs 16, 18. Since ends 36 and 38 have been oriented so that their directions are transverse to each other, their orientations are used to form the spring joint 34 illustrated in Figure 3. Left end 36 and right end 38 are subsequently closed to prevent the joint 34 from uncoupling.

10 Figure 4 illustrates a cross-sectional view of the sewing ring 14 with integral retaining springs 16, 18 of the present invention. Figure 5 illustrates how the sewing ring 14 is fastened to the base 40 of the outer stent 12. As shown in Figure 4, upper retaining spring 16 and lower retaining spring 18 are embedded within the silicone rubber sewing ring 14 by an insert molding or other suitable forming method known to those of skill in the art. The elastic material 42 that comprises the sewing ring 14 is also located between the spring coils of springs 16 and 18 thereby  
15 providing different retaining force characteristics than using two independent springs surrounded by a separate sewing ring, and also reducing spring vibration during the welding process. The cross-section of sewing ring 14 is generally triangular in shape. While this is the preferred configuration, many other configurations are also possible as will be apparent to one skilled in the art. The springs 16 and 18 are  
20 positioned within sewing ring 44 closer to one side of the sewing ring 44 to ensure that springs 16 and 18 will be able to exert sufficient clamping force against the base 40 of the outer stent 12. Springs 16 and 18 are fitted within grooves 44 and 46, respectively, of the base 42.

25 Since the springs 16 and 18 are integral to the elastic sewing ring 14, the vibrations caused by an ultrasonic welding process used to thermally bond the fabric cover 20 to the outer stent 12 do not cause the spring joint 34 to uncouple. Furthermore, springs insert molded as shown in the present invention do not translate circumferentially into undesirable areas, i.e., in the gaps along the base 40 of the stent 12 where the joint 34 would be left unsupported, on the outer stent 12  
30 during ultrasonic welding. With the present invention, even if the spring joints were to translate into gaps, the joints 34 would not become misaligned or uncoupled because the joints 34 would still be restrained from twisting by the elastic sewing ring 14. Having the spring joint 34 uncouple or become misaligned is undesirable since a less than optimum clamping force will be exerted on the tissue between the

stents.

5       FIG. 6 shows the sewing ring 14 along with the outer stent frame 12 and covering 20 to be used therewith. The sewing ring 14 is positioned about the base 40 of the outer stent frame 12 and then the covering 20 emplaced about the frame 12 and sewing ring 14. The completed outer stent is then ready to be mated with the inner stent 10, in the manner shown in FIG. 7.

10       While embodiments and applications of this invention have been shown and described, it should be apparent to those skilled in the art that many more modifications are possible without departing from the scope of the present invention.



WHAT IS CLAIMED IS:

1. A sewing ring for a tissue heart valve having an inner stent and an outer stent, said outer stent having a base with a plurality of grooves for receiving said sewing ring, said sewing ring comprising:

5 an elastic ring disposed around said base for allowing the securing of said outer stent to a patient; and

a plurality of retaining springs, each having a first end and a second end and comprised of a series of coils, said retaining springs being encapsulated within said elastic ring for securing said outer stent to said inner stent;

10 wherein each of said retaining springs has a spring joint formed by hooking a last half-coil of said first end of said spring with a last half-coil of said second end of said spring.

2. A sewing ring for a heart valve having an inner stent and an outer stent, said outer stent having a base with a groove for receiving said sewing ring, said sewing ring comprising:

15 an elastic ring for attachment to said base of said outer stent, said elastic ring allowing said valve to be secured to a patient; and

20 a retaining spring formed in a circle and encapsulated within said elastic ring for securing said outer stent to said inner stent, said spring positioned at a side of said elastic ring to be received in said groove, said encapsulation reducing the likelihood of said spring uncoupling from its circular configuration and thereby maintaining optimum clamping force between said outer stent and said inner stent.

25 3. The sewing ring of Claim 2, wherein said spring has a first end and a second end, said spring comprising a series of coils so that said circular configuration is formed by hooking a last half-coil of said first end with a last half-coil of said second end of said spring.

4. The sewing ring of Claim 2, wherein said elastic ring is formed of a silicone elastomer.

30 5. The sewing ring of Claim 4, wherein said spring is insert molded into said elastic ring.




FIG. 1a  
(PRIOR ART)




FIG. 1b  
(PRIOR ART)




FIG. 2  
(PRIOR ART)

2/5




FIG. 3

3/5

FIG. 4





FIG. 5

4/5




FIG. 6

5/5




FIG. 7

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US96/15026

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A61B 17/04; A61F 2/24

US CL : 606/148; 623/2

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 606/148, 623/2

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,163,955 A (LOVE et al) 17 November 1992, col. 11, lines 43-49, and 63-68; and col. 12, lines 1-7.	2, 4

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

Special categories of cited documents:		*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principles or theory underlying the invention
*A	document defining the general state of the art which is not considered to be of particular relevance		
*E	earliest document published on or after the international filing date	*X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*L	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Y	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*O	document referring to an oral disclosure, use, exhibition or other means		
*P	document published prior to the international filing date but later than the priority date claimed	*G	document member of the same patent family

Date of the actual completion of the international search

02 DECEMBER 1996

Date of mailing of the international search report

18 DEC 1996

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3590

Authorized officer

TINA T. D. PHAM

Telephone No. (703) 308-0824

Form PCT/ISA/210 (second sheet)(July 1992)\*

**THIS PAGE BLANK (USPTO)**



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**